

Q8 Axle Oil XG 80W-140

Description

Synthetic based automotive gear lubricant for hypoid axle transmissions

Application

- Rear axles and final drive applications. Approved by Scania in certain categories of use with extended drain application (180000 km)

Specifications

- API GL-4, API GL-5
- SAE J2360 / MIL-PRF-2105E
- Scania STO 1:0
- ZF TE-ML 05A, 07A, 12M, 16D, 17B

Benefits

- Extended drain capability
- Provides good wear protection under heavy duty condition
- Extends drive-line component life
- Satisfactory elastomer compatability
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 80W-140
Absolute Density, 15 °C	D 1298	kg/m ³	907
Kinematic Viscosity, 40 °C	D 445	mm ² /s	302
Kinematic Viscosity, 100 °C	D 445	mm ² /s	31
Viscosity Index	D 2270	-	142
Brookfield Viscosity, -12 °C	D 2983	Pa.s	-
Brookfield Viscosity, -26 °C	D 2938	Pa.s	140
Flash Point	D 93	°C	178
Pour Point	D 97	°C	-24

The figures above are not a specification. They are typical figures obtained within production tolerances.