

Q8 Chopin 68

Application

- Pneumatic tools and rock drill equipment
- Specification: ISO 6743-11, category PAC-PBC

Benefits

- No harmful or unpleasant odours due to careful component selection
- Outstanding protection against wear, rust and corrosion even in the presence of condensed water
- Excellent icing prevention through emulsification of water droplets
- High resistance against washing effect of water through strong oil film

| Properties | Method | Unit | Typical |
|--------------------------------|--------|--------------------|---------|
| ISO Viscosity Grade | - | - | 68 |
| Absolute Density, 15 °C | D 4052 | kg/m ³ | 880 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 68 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 8.66 |
| Flash Point | D 93 | °C | 236 |
| Flash Point | D 92 | °C | 262 |
| Pour Point | D 97 | °C | -21 |
| Appearance, 48 h, 4 °C | Visual | - | bright |
| Rust Test, Proc. A and B, 24 h | D 665 | - | pass |
| Saponification Number | D 94 | - | 3.0 |
| Phosphorus | XRF | % mass | 0.04 |
| Four Ball, Weld Load | D 2783 | N | 1700 |

The figures above are not a specification. They are typical figures obtained within production tolerances.