

# Q8 Formula Advanced Diesel 10W-40

## Description

Advanced Diesel Performance Synthetic Based Engine Oil

## Application

- High quality synthetic based engine oil formulated with Q8 hydrocracked base fluid.
- Specially recommended for high performance direct injection diesel engines.
- Recommended for passenger cars and vans with modern normally aspirated or turbocharged diesel engines.

## Specifications

- ACEA B4
- API CD,CF
- VW 505.00
- MB 229.1

## Benefits

- Synthetic based year round engine lubricant
- Good engine protection after cold starting
- Reduces engine fuel consumption
- Excellent engine performance under different driving circumstances
- Good protection against rust and corrosion
- Excellent soot control

Properties	Method	Unit	Typical
Viscosity Grade			SAE 10W-40
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	875
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	14.5
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	98.4
Viscosity Index	D 2270	-	153
Apparent Viscosity, -25 °C	IP 383	mPa.s	6580
Borderline Pumping Temperature	D 3829	°C	-30.3
Pour Point	D 97	°C	-30
Flash Point	D 93	°C	203
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

