

Q8 Formula Excel Diesel 5W-40

Description

Superior Diesel Performance Synthetic Engine Oil

Application

- High performance synthetic engine oil for passenger cars and vans with normally aspirated or turbocharged diesel engines.
- Specially recommended for high performance diesel engines and direct injection diesel engines.

Specifications

- ACEA A3/B4
- API CF
- MB 229.3
- VW 505.00
- GM LL-025B
- Renault RN 0700, RN 0710
- PSA B71 2300
- BMW Longlife-01
- Recommended for VW 505.01
- Recommended for Ford M2C 917-A
- JASO MA2

Benefits

- Synthetic year round engine lubricant
- Contains friction reducing components
- Excellent protection after cold starting
- Reduces fuel consumption
- Offers high oil film strength and thus limiting engine wear
- Excellent engine performance at different driving conditions
- Good protection against rust and corrosion
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Reduced environmental impact
- Excellent soot control

| Properties | Method | Unit | Typical |
|---|---------------|-------------------|-----------|
| Viscosity Grade | | | SAE 5W-40 |
| Absolute Density, 15 °C | D 4052 | kg/m ³ | 852 |
| Kinematic Viscosity, 100 °C | D 445 | °C | 13.9 |
| Kinematic Viscosity, 40 °C | D 445 | °C | 82 |
| Viscosity Index | D 2270 | - | 176 |
| Borderline Pumping Temperature | D 3829 | °C | -35 |
| Pour Point | D 97 | °C | -39 |
| Flash Point | D 93 | °C | 222 |
| Viscosity at high temp. & high shear rate | CEC-L-36-A-90 | mPa.s | >=3.5 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

