

Q8 Moto GT 10W-40

Description

High performance semi-synthetic engine oil for motorcycles with wet clutch systems requiring JASO MA, SAE 10W-40

Application

- All types of air cooled and water cooled four stroke motor cycle engines requiring JASO MA performance.

Recommendations

- Q8 Moto GT is recommended for severe everyday use of motor bikes and is suitable for use with lead free gasoline.

Specifications

- ACEA A3/B3
- JASO MA
- API SL

Benefits

- High performance JASO MA clutch friction performance
- Superior engine performance at extreme riding conditions
- Excellent engine protection after cold starting
- Offers high oil film strength and thus limiting engine wear
- Synthetic year round engine lubricant
- Provides sustained high oil pressure
- Prevents formation of black sludge
- Low volatility by use of synthetic base oils provides minimized oil consumption
- Good protection against rust and corrosion
- Reduced environmental impact
- Catalyst compatible lubricant

Properties	Method	Unit	Typical
Viscosity Grade			SAE 10W-40
Absolute Density, 15 °C	D 1298	kg/m ³	875
Kinematic Viscosity, 40 °C	D 445	mm ² /s	98.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.5
Viscosity Index	D 2270	-	152
Flash Point	D 93	°C	205
Pour Point	D 97	°C	-30

The figures above are not a specification. They are typical figures obtained within production tolerances.