



PLATINUM ULTOR MAXIMO 5W-30

Quality class: ACEA: E4, E7
Viscosity grad: SAE: 5W-30

GENERAL FEATURES:

Fully synthetic, best quality engine oil designed for use in highly loaded Diesel engines especially in big trucks, construction equipment and buses. It guarantees:

- long mileages between oil changes
- stable oil quality
- natural environment protection
- excellent characteristics in low temperatures
- maximum engine power in extreme conditions
- engine purity by keeping soot in a suspended matter
- reduced fuel and oil consumption
- long engine life
- reduced costs of fleet exploitation

APPLICATION:

Platinum Ultor Maximo 5W-30 is designed for use in modern Diesel engines with or without turbocharge, all year round. Due to perfectly selected base synthetic oils and refining additives, it provides ideal engine lubrication even in the most difficult exploitation conditions enabling it to achieve full power in any driving conditions.

It can be also applied in vehicles equipped with SCR system declared to meet Euro V requirements and in older vehicles meeting Euro IV and III requirements. It also meets EPA Tier I and II requirements concerning NOx and PM (particulate matter).

Platinum Ultor Maximo 5W-30 is an energy-saving oil. It guarantees lower fuel and oil consumption, long mileages between oil changes and natural environment protection.



STANDARDS, APPROVALS. SPECIFICATION:

VOLVO VDS-3,
MACK EO-N
RENAULT VI RLD-2
MB-APPROVAL 228.5
Meets requirements:
MAN M3277
MTU TYPE 3
RENAULT RVI RXD, RLD, RD-2
DAF EXTENDED DRAIN

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	5W-30
kinematic viscosity at 100°C	mm ² /s	12,3
viscosity index	-	163
pour point	°C	-40
flash point	°C	220
TBN	mg KOH/g	15,0
sulfated ash	%	1,9

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

