## **SAFETY DATA SHEET**

Q8 Heller 68



SECTION 1: Identification of the substance/mixture and of the company/ undertaking			
1.1 Product identifier			
Product name	: Q8 Heller 68		
Viscosity or Type	: ISO VG 68		
Material uses	: Lubricating oil for hydraulic equipment		
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b> Not applicable.			
1.3 Details of the supplier of	the safety data sheet		
Manufacturer / Distributor	: Kuwait Petroleum Companies in the Benelux Company Office: Brusselstraat 59, B-2018, Antwerp Contactaddress: Petroleumkaai 7, B-2020, Antwerp Tel. +32 3 247 38 11, Fax +32 3 216 03 42		
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communication preferably in English only.		
1.4 Emergency telephone nu	mber		
Europe	: +44 (0) 1235 239 670 CARECHEM24		
Global (English only)	: +44 (0) 1865 407 333		
SECTION 2: Hazards	identification		
2.1 Classification of the subs	stance or mixture		
Product definition	: Mixture		
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]		
The product is not classified Not classified.	as hazardous according to Regulation (EC) 1272/2008 as amended.		
Ingredients of unknown toxicity	: None.		
Ingredients of unknown ecotoxicity	: None.		
Classification according to			
•	as dangerous according to Directive 1999/45/EC and its amendments.		
Classification	: Not classified.		

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Not applicable.
Prevention	: Not applicable.
Response	: Not applicable.

Date of issue/Date of revision

1/13

Q8 Heller 68

Storage	:	Not applicable.
Disposal		Not applicable.
Supplemental label elements	:	Safety data sheet available on request.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	-	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.
Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.
Other hazards which do not result in classification	:	Defatting to the skin. Prolonged or repeated contact may dry skin and cause irritation.

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture					
			Clas	<b>Classification</b>		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥75 - <90	Not classified.	Not classified.	[2]	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥10 - <25	Not classified.	Asp. Tox. 1, H304	[1] [2]	
				See Section 16 for the full text of the H statements declared above.		

The mineral oils in the product contain < 3% DMSO extract (IP 346).

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

Q8 Heller 68

## **SECTION 4: First aid measures**

4.1 Description of first aid measures			
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.</li> </ul>		
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.		
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. High pressure skin injections are serious medical emergencies. Injury will not appear serious at first. Within a few hours, tissue will become swollen, discolored and extremely painful.		
Ingestion	: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.		

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sy	<u>mptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.

## SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	<ul> <li>Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides</li> </ul>

Q8 Heller 68

## **SECTION 5: Firefighting measures**

5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials fo	r c	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

4/13

Q8 Heller 68

### **SECTION 7: Handling and storage**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# 7.3 Specific end use(s)Recommendations: Not available.Industrial sector specific: Not available.

Industrial sector specific : N solutions

### **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Product/ingredient name	Exposure limit values
Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist
procedures atmosphere or b of the ventilation protective equip the following: E the assessment limit values and atmospheres - C of exposure to c (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as uropean Standard EN 689 (Workplace atmospheres - Guidance for of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 ospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance nethods for the determination of hazardous substances will also be

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available.

8.2 Exposure controls		
Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measu	ires	<u>5</u>
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

Q8 Heller 68

## SECTION 8: Exposure controls/personal protection

•	· · ·
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Wear suitable gloves tested to EN374. Recommended: Nitrile gloves.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties         Appearance         Physical state       : Liquid. [Oily liquid.]         Appearance       : Clear.         Color       : Yellow [Light]         Odor       : Characteristic.         Odor threshold       : Not available.         pH       : 7         Melting point/freezing point       : <-30°C         Initial boiling point and       : >300°C         boiling range       :         Flash point       : Open cup: >196°C [ASTM D92.]         Evaporation rate       : Not available.         Flasm point       : Open cup: >196°C [ASTM D92.]         Evaporation rate       : Not available.         Flasm point       : Open cup: >196°C [ASTM D92.]         Evaporation rate       : Not available.         Plantity (solid, gas)       : Not available.         Upper/lower flammability or explorable.       : Not available.         Vapor pressure       : <0.01 kPa [room temperature]         Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol//       : Not available.         wate			
Physical state:Liquid. [Oily liquid.]Appearance:Clear.Color:Yellow [Light]Odor:Characteristic.Odor threshold:Not available.pH:7Melting point/freezing point:<-30°CInitial boiling point and:>300°Cboiling range:Open cup: >196°C [ASTM D92.]Evaporation rate:Not available.Flash point:Open cup: >196°C [ASTM D92.]Evaporation rate:Not available.Flammability (solid, gas):Not applicable.Upper/lower flammability or explosive limits:Not available.Vapor pressure:<0.01 kPa [room temperature]Vapor density:Not available.Relative density:0.87Solubility(ies):Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water:>300°CAuto-ignition temperature:>300°CDecomposition temperature:>300°CViscosity (40°C):68 cStViscosity (40°C):68 cStViscosity (100°C):10.85 cSt	9.1 Information on basic physica	al a	nd chemical properties
Appearance: Clear.Color: Yellow [Light]Odor: Characteristic.Odor threshold: Not available.pH: 7Melting point/freezing point: <-30°CInitial boiling point and: >300°Cboiling range:Flash point: Open cup: >196°C [ASTM D92.]Evaporation rate: Not available.Flammability (solid, gas): Not available.Upper/lower flammability or: Not available.explosive limits: Not available.Vapor pressure: <0.01 kPa [room temperature]Vapor density: Not available.Relative density: 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not available.water: >300°CViscosity (40°C): 68 cStViscosity (10°C): 10.85 cSt	<u>Appearance</u>		
Color:Yellow [Light]Odor:Characteristic.Odor threshold:Not available.pH:7Melting point/freezing point:<-30°CInitial boiling point and:>300°Cboiling range:Open cup: >196°C [ASTM D92.]Evaporation rate:Not available.Flash point:Open cup: >196°C [ASTM D92.]Evaporation rate:Not available.Flammability (solid, gas):Not applicable.Upper/lower flammability or explosive limits:Not available.Vapor pressure:<0.01 kPa [room temperature]Vapor density:0.87Solubility(ies):Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water:Not available.Auto-ignition temperature:>300°CViscosity (40°C):68 cStViscosity (100°C):10.85 cSt	Physical state	:	Liquid. [Oily liquid.]
Odor: Characteristic.Odor threshold: Not available.pH: 7Melting point/freezing point: <-30°CInitial boiling point and boiling range: >300°CFlash point: Open cup: >196°C [ASTM D92.]Evaporation rate: Not available.Flammability (solid, gas): Not available.Upper/lower flammability or explosive limits: Not available.Vapor pressure: <0.01 kPa [room temperature]Vapor density: 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: >300°CViscosity (40°C): 68 cStViscosity (40°C): 10.85 cSt	Appearance	1	Clear.
Odor threshold:Not available.pH:7Melting point/freezing point:<-30°CInitial boiling point and:>300°Cboiling range:>300°CFlash point:Open cup: >196°C [ASTM D92.]Evaporation rate:Not available.Flammability (solid, gas):Not available.Upper/lower flammability or:Not available.explosive limits:Not available.Vapor pressure:<0.01 kPa [room temperature]Vapor density:Not available.Relative density:0.87Solubility(ies):Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/:Not available.water:>300°CViscosity (40°C):68 cStViscosity (100°C):10.85 cSt	Color	:	Yellow [Light]
pH       : 7         Melting point/freezing point       : <-30°C         Initial boiling point and       : >300°C         boiling range       :         Flash point       : Open cup: >196°C [ASTM D92.]         Evaporation rate       : Not available.         Flammability (solid, gas)       : Not available.         Upper/lower flammability or explosive limits       : Not available.         Vapor pressure       : <0.01 kPa [room temperature]         Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/ water       : Not available.         Auto-ignition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	Odor	:	Characteristic.
Melting point/freezing point:<-30°C	Odor threshold	:	Not available.
Initial boiling point and boiling range: >300°CFlash point: Open cup: >196°C [ASTM D92.]Evaporation rate: Not available.Flammability (solid, gas): Not applicable.Upper/lower flammability or explosive limits: Not available.Vapor pressure: <0.01 kPa [room temperature]Vapor density: Not available.Relative density: 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: >300°CViscosity (40°C): 68 cStViscosity (100°C): 10.85 cSt	рН	:	7
boiling rangeFlash point: Open cup: >196°C [ASTM D92.]Evaporation rate: Not available.Flammability (solid, gas): Not applicable.Upper/lower flammability or explosive limits: Not available.Vapor pressure: <0.01 kPa [room temperature]Vapor density: Not available.Relative density: 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/: Not available.water: >300°CDecomposition temperature: >300°CViscosity (40°C): 68 cStViscosity (100°C): 10.85 cSt	Melting point/freezing point	:	<-30°C
Flash point       : Open cup: >196°C [ASTM D92.]         Evaporation rate       : Not available.         Flammability (solid, gas)       : Not applicable.         Upper/lower flammability or explosive limits       : Not available.         Vapor pressure       : <0.01 kPa [room temperature]         Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/ water       : Not available.         Auto-ignition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	• •	:	>300°C
Evaporation rate       : Not available.         Flammability (solid, gas)       : Not applicable.         Upper/lower flammability or explosive limits       : Not available.         Vapor pressure       : <0.01 kPa [room temperature]         Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/       : Not available.         water       : >300°C         Decomposition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	boiling range		
Flammability (solid, gas)       : Not applicable.         Upper/lower flammability or explosive limits       : Not available.         Vapor pressure       : <0.01 kPa [room temperature]         Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/       : Not available.         water       : >300°C         Decomposition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	Flash point	:	Open cup: >196°C [ASTM D92.]
Upper/lower flammability or explosive limitsNot available.Vapor pressure vapor density: <0.01 kPa [room temperature]Vapor density Relative density: Not available.Relative density Solubility(ies): 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature Upecomposition temperature: >300°CViscosity (40°C) 	Evaporation rate	:	Not available.
explosive limitsVapor pressure: <0.01 kPa [room temperature]Vapor density: Not available.Relative density: 0.87Solubility(ies): Insoluble in the following materials: cold water and hot water.Partition coefficient: n-octanol/ water: Not available.Auto-ignition temperature: >300°CDecomposition temperature: >300°CViscosity (40°C): 68 cStViscosity (100°C): 10.85 cSt	Flammability (solid, gas)	1	Not applicable.
Vapor density       : Not available.         Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/ water       : Not available.         Auto-ignition temperature       : >300°C         Decomposition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt		:	Not available.
Relative density       : 0.87         Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/       : Not available.         water       .         Auto-ignition temperature       : >300°C         Decomposition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	Vapor pressure	:	<0.01 kPa [room temperature]
Solubility(ies)       : Insoluble in the following materials: cold water and hot water.         Partition coefficient: n-octanol/ water       : Not available.         Auto-ignition temperature       : >300°C         Decomposition temperature       : >300°C         Viscosity (40°C)       : 68 cSt         Viscosity (100°C)       : 10.85 cSt	Vapor density	:	Not available.
Partition coefficient: n-octanol/ : Not available.         water         Auto-ignition temperature : >300°C         Decomposition temperature : >300°C         Viscosity (40°C) : 68 cSt         Viscosity (100°C) : 10.85 cSt	Relative density	1	0.87
waterAuto-ignition temperature: >300°CDecomposition temperature: >300°CViscosity (40°C): 68 cStViscosity (100°C): 10.85 cSt	Solubility(ies)	:	Insoluble in the following materials: cold water and hot water.
Decomposition temperature: >300°CViscosity (40°C): 68 cStViscosity (100°C): 10.85 cSt		1 :	Not available.
Viscosity (40°C)         : 68 cSt           Viscosity (100°C)         : 10.85 cSt	Auto-ignition temperature	:	>300°C
Viscosity (100°C) : 10.85 cSt	Decomposition temperature	:	>300°C
	Viscosity (40°C)	1	68 cSt
Date of issue/Date of revision       : 11-01-2015       Date of previous issue       : No previous validation       Version       : 1	Viscosity (100°C)	:	10.85 cSt
	Date of issue/Date of revision	: 1	1-01-2015 Date of previous issue : No previous validation Version : 1

6/13

Q8 Heller 68

## SECTION 9: Physical and chemical properties

Explosive properties

: Not applicable.

Oxidizing properties

: Not applicable.

#### 9.2 Other information

No additional information.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

## **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours
	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-

Conclusion/Summary

: Not available.

#### Acute toxicity estimates

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Edema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Edema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours

Q8 Heller 68

SECTION 11: Toxicological information					
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
Conclusion/Summary	: Not available.	·			

#### **Sensitization**

Product/ingredient name	Route of exposure	Species	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	skin	Guinea pig	Not sensitizing
Distillates (petroleum), solvent-dewaxed heavy paraffinic	skin	Guinea pig	Not sensitizing

#### **Conclusion/Summary** : Not available.

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo	Negative
		Subject: Mammalian-Animal Cell: Somatic	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo	Negative
•		Subject: Mammalian-Animal Cell: Somatic	

Conclusion/Summary

: Not available.

#### **Carcinogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal - TC	Mouse - Female	-	78 weeks
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal - TC	Mouse - Female	-	78 weeks

**Conclusion/Summary** : Not available.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

**Conclusion/Summary** : Not available.

#### **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Q8 Heller 68

18 Heller 68					
	logical information				
Conclusion/Summary	: Not available.				
Specific target organ toxic	<u>ity (single exposure)</u>				
Not available.					
Specific target organ toxic Not available.	<u>ity (repeated exposure)</u>				
Aspiration hazard					
Product	ingredient name		Result		
Distillates (petroleum), solve	ent-dewaxed heavy paraffinic	ASPIRATIO	ON HAZARD - Cate	egory 1	
nformation on the likely outes of exposure	: Not available.				
otential acute health effect	\$				
Eye contact	<ul> <li>No known significant effects</li> </ul>	or critical hazard	IS.		
Inhalation	: No known significant effects				
Skin contact	: Defatting to the skin. May c				
Ingestion	: No known significant effects	-			
-	0				
ymptoms related to the ph	<u>ysical, chemical and toxicologi</u>	ical characteristi	<u>ics</u>		
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking				
Ingestion	: No specific data.				
alayed and immediate offe	cts and also chronic effects fro	m chort and lon			
<u>Short term exposure</u>			<u>ig term exposure</u>		
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
<u>Long term exposure</u>					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Potential chronic health eff	fects	1			
Product/ingredient name	Result	Species	Dose	Exposure	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week	
· · · · · · · · · · · · · · · · · · ·	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
	Sub-acute NOAEL Inhalation Dusts and mists	Rat - Male	>980 mg/m³	4 weeks; 5 day	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	per week 13 weeks; 5 days per week	
Paramino	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day	
	Sub-acute NOAEL Inhalation	Rat - Male	>980 mg/m³	4 weeks; 5 days	

Q8 Heller 68

## **SECTION 11: Toxicological information**

Conclusion/Summary	: Not available.
General	<ul> <li>Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.</li> </ul>
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Other information	: Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Conclusion/Summary** : Not available.

#### 12.2 Persistence and degradability

Conclusion/Summary	: Not available.		
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Inherent Inherent

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic	>3 >3	-	low low

#### 12.4 Mobility in soil

Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment		
PBT	: Not applicable.	
vPvB	: Not applicable.	

**12.6 Other adverse effects** : No known significant effects or critical hazards.

Q8 Heller 68

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation		
13 01 10*	mineral based non-chlorinated hydraulic oils		
Packaging			
Methods of disposal	<ul> <li>The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.</li> </ul>		
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		

### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to Annex II of MARPOL 73/78 and the IBC Code

Q8 Heller 68

## **SECTION 15: Regulatory information**

15.1 Safety, health and er <u>EU Regulation (EC) No.</u>	ivironmental regulations/legislation specific for the substance or mixture
	stances subject to authorization
Annex XIV	
None of the component	s are listed.
Substances of very hi	<u>gh concern</u>
None of the component	s are listed.
Other EU regulations	
Europe inventory	: Not determined.
Seveso II Directive	
This product is not contro	olled under the Seveso II Directive.
Hazard class for water (WGK)	: 1 Appendix No. 4
International regulations	
Chemical Weapon Conv	ention List Schedules I, II & III Chemicals
Not listed.	
Montreal Protocol (Anne	xes A, B, C, E)
Not listed.	
Stockholm Convention	on Persistent Organic Pollutants
Not listed.	
	on Prior Inform Consent (PIC)
Not listed.	
UNECE Aarhus Protocol	on POPs and Heavy Metals
Not listed.	
International lists	
National inventory	
Australia	: Not determined.
Canada	: Not determined.
China	: All components are listed or exempted.
Japan	: Not determined.
Malaysia	: Not determined.
New Zealand	: All components are listed or exempted.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
United States	: All components are listed or exempted.
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Q8 Heller 68

SECTION 16: Other information		
Abbreviations and	: ATE = Acute Toxicity Estimate	
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.	
	1272/2008]	
	DMEL = Derived Minimal Effect Level	
	DNEL = Derived No Effect Level	
	EUH statement = CLP-specific Hazard statement	
	PBT = Persistent, Bioaccumulative and Toxic	
	PNEC = Predicted No Effect Concentration	
	RRN = REACH Registration Number	
	vPvB = Very Persistent and Very Bioaccumulative	

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification	
Not classified.			
Full text of abbreviated H statements	: H304 May be fatal if s	wallowed and enters airways.	
Full text of classifications [CLP/GHS]	: Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1	
Full text of abbreviated R phrases	: Not applicable.		
Full text of classifications [DSD/DPD]	: Not applicable.		
Date of printing	: 11-01-2015		
Date of issue/ Date of revision	: 11-01-2015		
Date of previous issue	: No previous validation		
Version	: 1		
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands		
Notice to reader			

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.