

Q8 Scooter City Mix

Description

Self-mixing two-stroke gasoline engine lubricant

Application

- Two-stroke air cooled gasoline engines running under high temperature, high load conditions and with lean oil/fuel mixtures (2%)

Recommendations

- Q8 City Mix may be used in air cooled high performance two-stroke gasoline engines for on-land use such as for motor scooters, motor cycles
- and chainsaw applications with premix or oil injection. Suitable for leadfree gasoline.

Specifications

- Jaso FB
- API-TC

Benefits

- Excellent cylinder and bearing lubrication
- Outstanding low temperature fluidity
- Low ash additive system prevents deposits
- Reduced exhaust system blockage
- Outstanding high temperature deposit control
- Reduced spark plug fouling and deposit induced preignition
- Prevents piston ring sticking
- Improved anti-rust and corrosion protection
- Self mixing in oil injection systems and premix application (SAE class 3)

Properties	Method	Unit	Typical
Absolute Density, 15 °C	D 1298	kg/m ³	874
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.3
Viscosity Index	D 2270	-	104
Sulfated Ash	D 874	% mass	0.1
Flash Point	D 93	°C	91
Pour Point	D 97	°C	-30

The figures above are not a specification. They are typical figures obtained within production tolerances.