

Q8 T 35 SAE 80W

Description

Automotive transmission lubricant

Application

- In moderate duty drive-line components especially synchromesh manual transmissions

Recommendations

- Q8 T 35 may be used as gear lubricant in drive-line components, when one or more of the following specifications are used to describe the required lubricant quality:

Specifications

- API GL-4
- John Deere JDM J11B (manual transmissions)
- Eaton Bulletin 2053 (manual transmissions, oil temp. < 110 °C)
- Eaton/Fuller Bulletin 2052 (twin countershaft transmissions, oil temp. < 110 °C)
- Ford SM-2C-1011A (commercial gearboxes)
- Ford SQM-2C9008-A (manual transmissions)
- Fuller Form 121 (manual transmissions, R and RT series, oil temp. < 110 °C)
- General Motors Pt. no. 19 40 75 (90 001 777) (manual transmissions)
- MAN 341 Z-1/E-1/Z-2 (manual transmissions)
- MB Approval 235.1
- ZF TE-ML 02B (truck and bus transmissions)
- ZF TE-ML 08 (steering systems)
- ZF TE-ML 17A (transmissions and axles lift trucks)
- ZF TE-ML 16A (SAE 90, transmissions for rail vehicles)
- ZF TE-ML 19A (Transfer and offset transmissions for commercial vehicles)

Benefits

- Excellent gear shifting
- Limits synchromesh wear
- Protects against gear wear and extends equipment life
- Stay-in grade shear stability
- Prohibits corrosion and protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 80W
Absolute Density, 15 °C	D 1298	kg/m ³	882
Kinematic Viscosity, 40 °C	D 445	mm ² /s	70.1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.25
Viscosity Index	D 2270	-	108
Brookfield Viscosity, -26 °C	D 2938	Pa.s	30
Brookfield Viscosity, -40 °C	D 2938	Pa.s	-
Flash Point	D 93	°C	166
Pour Point	D 97	°C	-30

The figures above are not a specification. They are typical figures obtained within production tolerances.