

## DELGAS A 15W-40

Viscosity grad: SAE: 15W-40

### GENERAL FEATURES:

High-quality, multi-grade, ash-free oil for stationary gas engines, developed based on highly refined base oils with a selection of enhancement additives. Owing to its properties, it helps to keep the engine clean at all times and reduce contamination on spark plugs. The oil does not contain Bright Stock and, therefore, prevents the formation of carbon deposits and channel clogging in two-stroke engines. Advantages:

- excellent thermal stability
- resistance to oxidation and nitration
- excellent wear protection
- excellent protection against deposit formation
- excellent anti-corrosion properties
- good low-temperature properties

### APPLICATION:

Delgas A 15W-40 is an ash-free oil intended for use in two-stroke natural gas-propelled engines, such as: Ajax, Cooper-Bessemer, Clark and Fairbanks-Morse, operating in gas transfer and compression stations.

PARAMETERS	UNIT	TYPICAL VALUES
LepKinematic viscosity at 40°C	mm <sup>2</sup> /s	104,4
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	14,1
Viscosity index	-	137
Flow temperature	°C	-30
Flash point acc. to open cup method	°C	218
Sulphated ash	% m/m	0,006

#### NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

