



## FRIGOL POE 68

Viscosity grad: ISO VG: 68

### GENERAL FEATURES:

FRIGOL POE oils are fully synthetic, polyester (POE) oils, intended for use in refrigeration compressors and air conditioners with such liquids as HFC, CFC or HCFC as refrigerants.

### APPLICATION:

Thanks to their accurately selected synthetic oil basis and an adequate package of additives, Frigol POE oils guarantee:

- high thermal stability,
- high chemical stability,
- high adaptability to all refrigerating systems,
- ideal protection of lubricated elements against wear,
- ideal protection of steel and aluminum elements,
- extended efficiency and durability of refrigerating systems,
- ideal for devices with HFC – R134a, CFC – R11, R12, HCFC – R142, R407C and R410 as refrigerants

### Remarks:

Frigol POE is not recommended for ammonia systems



## Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
Density at 15 °C	g/cm <sup>3</sup>	0,968
Viscosity index	-	108
Appearance at 20°C	-	Clear, homogenous liquid
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	68,0
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	9,1
Density at 20°C	kg/m <sup>3</sup>	0,964
Flash point	°C	260
Pour point	°C	-42
Water content	mg/kg	<50

**NOTE:**  
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

