

L-AN Z 15 MACHINE OIL

Viscosity grad: Depending on the kinematic viscosity at 40°C, the LAN (Z) low-solidifying oils are available in three classes marked with numbers according to PN-78/C-96098: 7, 10, 15, 22, 32, 46, 68, 100

GENERAL FEATURES:

L-AN (Z) low-solidifying machine oils are manufactured from refined oil distillates sourced from petroleum processing and additives reducing the solidification point.

APPLICATION:

L-AN Z machine oils are intended mainly for lubricating of light and medium loaded machine elements and industrial devices e.g.

- rolling bearings and slide bearings,
 - guides ,
 - mechanical gears,
 - spindles, etc.,
 - and supplementary friction centres which are exposed to low temperatures i.e. operating in unheated rooms in winter.
- Some L-AN (Z) low-solidifying machine oils can also be applied for other purposes e.g. hydraulic systems.

STANDARDS, APPROVALS. SPECIFICATION:

PN-88/C-96071

PARAMETERS	UNIT	TYPICAL VALUES
Kinematic viscosity at 40°C	mm ² /s	15.2
Viscosity index	-	97
Flow temperature	°C	-33

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

