

ORLEN OIL MONSUN PLUS 15W-40

Quality class: API: CH-4
Viscosity grad: SAE: 15W-40

GENERAL FEATURES:

Orlen Oil Monsun Plus is an engine oil composed of high quality basic mineral oils and upgrading additives (antioxidizers, corrosion inhibitors, additives improving cleaning, dispersing and lubricating properties, viscosity and temperature resistance), use of which reduces the wear and tear of engine components and prevents the occurrence of carbon formation and deposits. Moreover, the oil meets the requirements for emission of harmful components of exhaust gas.

APPLICATION:

The oil is intended to lubricate four-stroke diesel engines. It is particularly suitable to use in high-power diesel engines operating in heavy duty conditions with or without turbo. The oil is particularly recommended for use in ship engines, in cases where the manufacturer recommends the use of an oil of this quality and viscosity class. It is suitable for engines powered by fuels with low sulphur content.

STANDARDS, APPROVALS. SPECIFICATION:

The oil meets the requirements of:
MAN M 3275,
Caterpillar CAT ECF-1,
MACK EO-M Plus,
VOLVO VDS-2

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity class	-	15W-40
Kinematic viscosity at 100°C	mm ² /s	14,4
Viscosity index	-	130
Pour point	°C	-30
Flash point	°C	215
Base number TBN	mg KOH/g	14,3

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.