

PLATINUM MULTI STOU 10W-40

Quality class: API: CG-4 API: GL-4
Viscosity grad: SAE: 10W-40

GENERAL FEATURES:

Platinum Multi STOU 10W-40 is a high-quality synthetic oil of the Super Tractor Oil Universal type. It is characterised by a very high level of protection for engines working in difficult conditions. Thanks to its carefully chosen formulation it provides excellent lubrication for all kinds of manual transmissions, PowerShifts and CVTs.

APPLICATION:

Platinum Multi STOU 10W-40 is a universal oil which can be used in machine engines, manual gearboxes, PowerShifts and CVTs. It can be successfully used in hydraulic systems and wet brakes.

STANDARDS, APPROVALS. SPECIFICATION:

Meets the requirements of:

Massey Ferguson M1145
Massey Ferguson M1144
NH024C
Ford M2C 159B3
Ford M2C 159C3
John Deere J27
New Holland 82009203
Ford M2C134D
Case MS1205
Case MS1206
Case MS1209
Allison C-4
Caterpillar TO-2
ZF 06B, ZF 06C, ZF 07B
ZF 03A, ZF 05K ZF 07D
MB 227.1
MB 228.1

CCMS D4
Sperry Vickers/Eaton: M2950S
Sperry Vickers/Eaton: I-280-S



Sauer Sundstrand/Danfoss: Hydro Static Trans Fluid
AFNOR NFE68603E

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	10W-40
kinematic viscosity at 100°C	mm ² /s	14,4
viscosity index	-	153
flow temperature	°C	-45
flash-point	°C	216

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

