



PLATINUM MaxExpert FT 5W-30

Quality class: ACEA: C2
API: SM/CF
Viscosity grad: SAE: 5W-30

GENERAL FEATURES:

Platinum MaxExpert FT 5W-30 is a high quality engine oil, designed on the basis of Complex Protection Formula. It enables to protect the drive unit during cold start, when it is most vulnerable to damage. Platinum MaxExpert 5W-30 also prevents the deposits formation in the turbo supercharged engines, greatly extending its life. The engine tests confirmed reduction of frictional resistance what results in a decrease in fuel consumption.

It guarantees:

- Engine protection against deposits formation,
- Protection of turbocompressor proven in engine tests,
- Compatibility with exhaust gas treatment systems of Euro 6 engines thanks to reduced content of SAPS.

APPLICATION:

Formulation of Platinum MaxExpert FT 5W-30 oil was designed for Fiat, Lancia and Alfa Romeo vehicles. Especially recommended for use in engines requiring FIAT 9.55535-S1 approval. It can be applied in gasoline engines and diesel engines both turbocharged and naturally aspirated. It protects exhaust gas treatment systems thanks to low content of sulfur and sulfated ash.

STANDARDS, APPROVALS. SPECIFICATION:

Meet requirements:
FIAT 9.55535-S1

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	5W-30
kinematic viscosity at 100°C	mm ² /s	10,3
viscosity index	-	160
pour point	°C	-30
total base number	Mg KOH/g	8,1
sulphated ash	%	0,73

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

