



PLATINUM RIDER RACING 2T

Quality class: API: TC
JASO: FD
ISO-L-EGD

GENERAL FEATURES:

Fully synthetic oil designed for modern high-stroke motorcycle engines. The unique HTS (High Temperature Stability) formula provides effective lubrication at high temperatures for touring and sports motorcycles. At the same time, it ensures low oil consumption and maximum engine protection. It meets the highest quality specification of JASO (Japanese Automotive Standards Organization) and has the reliability guarantee of the motorcycle "ORLEN TEAM".

Oil well miscible with fuel, guarantees clean combustion.

Dosage: in accordance with engine manufacturer's recommendations, 2% oil to fuel ratio /1:50/ if the engine manufacturer does not recommend otherwise.

APPLICATION:

Designed for lubrication of two-stroke sport motorcycle engines, especially cross and trial, as well as sport ATVs, scooters and mopeds. Suitable for mixing or individual lubrication.

PARAMETERS	UNIT	TYPICAL VALUES
Kinematic viscosity at 100°C	mm ² /s	6,8
Viscosity index	-	160
Pour point	°C	-35
Flash point	°C	80

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

