



Platinum GEAR ATF III

Quality class: GM Dexron® III G
Ford MERCON®

GENERAL FEATURES:

Platinum GEAR ATF III is manufactured with special semisynthetic technology supported by a set of enriching additives with antioxidative and anticorrosive properties and ones improving lubricating properties as well as resistance to foaming.

APPLICATION:

Platinum GEAR ATF III is intended for automatic gears of cars, trucks and buses, manufacturer of which recommends application of Dexron® III oils. Platinum GEAR ATF III is also recommended for power steering devices, hydraulic clutches of cars and trucks and for ATF requiring hydraulic systems. It can also be used in Powershift gears in tractors and loaders where the manufacturer recommends the use of ATF oil.

STANDARDS, APPROVALS. SPECIFICATION:

It meets requirements of the following:

ALLISON C-4;
ZF TE-ML 03D, 04D, 09, 14A, 17C;
VOITH H 55.633535;
MAN 339 typ V-1 (ex MAN 339 typ F);
MAN 339 typ Z-1 (ex MAN 339 typ F);
Mercedes Benz 236.5
Mercedes Benz 236.9

PARAMETERS	UNIT	TYPICAL VALUES
Kinematic viscosity at 100°C	mm ² /s	7.2
Flow temperature	°C	-45
Ignition temperature	°C	201

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

