

## Q8 Dynobear 3

### Application

- Q8 Dynobear 3 is an industrial lubricant developed for the lubrication of spindle bearings. It contains oiliness additives to eliminate the stick-slip effect and to reduce friction.

### Specifications

- ISO 6743-2

### Benefits

- Optimum anti-friction due to oiliness additives
- Long service life due to thermal and oxidation stability
- No judder due to stick slip properties

### Features and Benefits

- Optimum anti-friction due to oiliness additives
- Long service life due to thermal and oxidation stability
- No judder due to stick slip properties

Properties	Method	Unit	Typical
Viscosity Grade	-	-	3
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	814
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	3.476
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	1.33
Viscosity Index	D 2270	-	100
Flash Point	D 92	°C	144
Pour Point	D 97	°C	-24
Copper Strip, 3 h, 100 °C	D 130	-	1a
Total Acid Number	D 974	mg KOH/g	0.3
Colour	D 1500	-	L1.0

*The figures above are not a specification. They are typical figures obtained within production tolerances.*

