

# Q8 Holst XEP 46

## Description

Hydraulic systems equipped with fine filters, or systems not compatible with zinc based anti-wear hydraulic oils

## Specifications

- ISO 11158, category HM
- DIN 51524, Part 2, category HLP
- ISO 6743-4, category HM
- DIN 51502, category HLP

## Benefits

- Suitable for most hydraulic equipment through its outstanding anti-wear performance
- Q8 Holst XEP meets the Brugger test requirement (>50 N/mm<sup>2</sup>) for hydraulic oils
- Long service life due to high oxidation stability
- Reliable operation of sensitive hydraulics such as servo systems and robotics through outstanding demulsibility and filterability

## References

- Q8 Holst XEP provides highest performance in systems sensitive to environmental contaminants and therefore equipped with fine filtration systems

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	875
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	6.72
Viscosity Index	D 2270	-	98
Flash Point	D 92	°C	222
Pour Point	D 97	°C	-18
Colour	D 1500	-	L1.0
Copper Strip, 3 h, 100 °C	D 130	-	1
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Total Acid Number	D 974	mg KOH/g	0.40
Emulsion, Distilled Water, 82.2 °C	D 1401	-	40-40-0 (10)
Air Release, 50 °C	DIN 51381	min	4
Foam, 5 min blowing, seq. 1/2/3	D 892	ml	0/10/0
10 min settling, seq. 1/2/3		ml	0/0/0
Oxidation, Time to 2.0 TAN	D 943	h	2500
FZG Test, A/8.3/90	DIN 51354	load stage	>12
Brugger Test	-	N/mm <sup>2</sup>	>50

The figures above are not a specification. They are typical figures obtained within production tolerances.