

TRANSGEAR PE 150

Quality class: ISO 12925-1 CKD/CKS/CKT
Viscosity grad: ISO VG: 150

GENERAL FEATURES:

Transgear PE 150 industrial gear synthetic oils are manufactured basing on poly-alpha-olefines (PAO) and esters as well as specially selected enriching additives.

They were developed especially to work with very high loads and high temperature.
It is featured by:

- ability to transfer extremely high loads and perfect protection of gear elements from micropitting,
- high resistance to aging and high anticorrosive protection,
- perfect ability to be filtered and wide range of operation temperatures,
- extended interchange period.

APPLICATION:

Transgear PE 150 oils are intended to lubricate any kind of heavy-duty toothed gears of industrial machines and devices endangered by micropitting, working in the temperatures up to 180oC including: spur cylindrical gears, helical bevel gears, spiral bevel gears and worm gears exposed to heavy thermal loads as well as rolling bearings and sliding bearings.

Due to unique lubricating and antioxidative properties they are also recommended for lubricating turbine gears working in heavy conditions.

STANDARDS, APPROVALS. SPECIFICATION:

Meet requirements:

Siemens MD – Flender v.13
US Steel 224
AGMA 9005-EO2 (EP)
David Brown S1.53.101 type E
DIN 51517 part 3 – CLP
Cincinnati Machine P-74



Physical and chemical properties:

PARAMETERS	UNIT	TYPICAL VALUES
Kinematic viscosity at 40°C	mm ² /s	152
Viscosity index	-	147
Flow temperature	°C	-40
Ignition temperature	°C	240
Corrosiveness to copper 3 h/100°C, corrosion rate,	reference sample	1b

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

