Q8 Mozart 520 SAE 30

Monogrades

Description
Universal engine and transmission lubricant

Application
- In all high performance four stroke diesel engines, normally aspirated as well as turbo-charged or supercharged, operating under moderate to heavy duty conditions where normal or moderately extended oil drain intervals are applied

Recommendations
- Q8 Mozart 520 Monograde may be used as engine oil in vessels, when one or more of the following specifications are used to describe the required lubricant quality

Specifications
- API CG-4/SJ
- ACEA B2/E2
- MAN 270 (diesel engines, normal drain)
- Mercedes-Benz 227.0
- Mercedes-Benz 228.0

Benefits
- Universal product limits engine/transmission wear
- Prohibits corrosion and rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 30
Absolute Density, 15 °C	D 4052	g/ml	0.890
Kinematic Viscosity, 40 °C	D 445	mm²/s	100.6
Kinematic Viscosity, 100 °C	D 445	mm²/s	11.93
Viscosity Index	D 2270	-	108
Flash Point	D 93	°C	208
Pour Point	D 97	°C	-21
Total Base Number	D 2896	mg KOH/g	8.5
Sulphated Ash Content	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.