

SAFETY DATA SHEET

Q8 Mozart MS 50 SAE 40



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Q8 Mozart MS 50 SAE 40
Viscosity or Type : SAE 40
Material uses : Lubricating oil for marine engines

1.2 Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Distributor : Kuwait Petroleum Companies in the Benelux
Company Office: Brusselstraat 59, B-2018, Antwerp
Contactaddress: Petroleumkaai 7, B-2020, Antwerp
Tel. +32 3 247 38 11, Fax +32 3 216 03 42

e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only.

1.4 Emergency telephone number

Europe : +44 (0) 1235 239 670
Global (English only) : +44 (0) 1865 407 333



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Skin Sens. 1, H317
Repr. 1B, H360FD (Fertility and Unborn child)
Aquatic Chronic 3, H412

Ingredients of unknown toxicity : None.

Ingredients of unknown ecotoxicity : None.

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Repr. Cat. 2; R60
R43
R52/53

Human health hazards : May impair fertility. May cause sensitization by skin contact.


Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

SECTION 2: Hazards identification

| | | |
|---|---|---|
| Hazard pictograms | : |  |
| Signal word | : | Danger |
| Hazard statements | : | H317 - May cause an allergic skin reaction. H360FD - May damage fertility. May damage the unborn child. H412 - Harmful to aquatic life with long lasting effects. |
| <u>Precautionary statements</u> | | |
| General | : | Not applicable. |
| Prevention | : | P201 - Obtain special instructions before use. P280 - Wear protective gloves. P273 - Avoid release to the environment. |
| Response | : | P308 + P313 - IF exposed or concerned: Get medical attention. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. |
| Storage | : | P405 - Store locked up. |
| Disposal | : | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Hazardous ingredients | : | LOB Calcium long chain alkaryl sulphonate Calcium long chain alkaryl sulphonate Branched alkylphenol and Calcium branched alkylphenol |
| Supplemental label elements | : | Not applicable. |
| Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles | : | Restricted to professional users. |
| <u>Special packaging requirements</u> | | |
| Containers to be fitted with child-resistant fastenings | : | Not applicable. |
| Tactile warning of danger | : | Not applicable. |
| 2.3 Other hazards | | |
| Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII | : | Not applicable. |
| Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII | : | Not applicable. |
| Other hazards which do not result in classification | : | Defatting to the skin. Prolonged or repeated contact may dry skin and cause irritation. |

Q8 Mozart MS 50 SAE 40

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Classification | | Type |
|---|--|-------------|--|--|------|
| | | | 67/548/EEC | Regulation (EC) No. 1272/2008 [CLP] | |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6 | ≥75 - <90 | Not classified. | Not classified. | [2] |
| Phenol, 2,2'-polythiobis [4-C8-30-alkyl derivs., calcium salts, overbased | REACH #: 01-2119524004-56 EC: 291-829-9 CAS: 90480-91-4 | ≥5 - <10 | R53 | Aquatic Chronic 4, H413 | [1] |
| Calcium long chain alkaryl sulphonate polymer | - | ≥1 - <3 | R53 | Aquatic Chronic 4, H413 | [1] |
| LOB Calcium long chain alkaryl sulphonate | - | ≥1 - <3 | R43 R53 | Skin Sens. 1, H317 Aquatic Chronic 4, H413 | [1] |
| Branched alkylphenol and Calcium branched alkylphenol | - | ≥0.3 - <1 | Repr. Cat. 2; R60 Xi; R36/38 N; R50/53 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 1B, H360FD (Fertility and Unborn child) Aquatic Chronic 1, H410 | [1] |
| Hindered alkylphenol | - | ≥0.1 - <0.3 | Xi; R36/38 N; R50/53 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 | [1] |
| | | | See Section 16 for the full text of the R-phrases declared above. | See Section 16 for the full text of the H statements declared above. | |

The mineral oils in the product contain < 3% DMSO extract (IP 346).

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

SECTION 4: First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Q8 Mozart MS 50 SAE 40

SECTION 4: First aid measures

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, alcohol-resistant foam or water spray (fog).

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides
metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Q8 Mozart MS 50 SAE 40

SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|---|--|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist |

Q8 Mozart MS 50 SAE 40

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.

Q8 Mozart MS 50 SAE 40

SECTION 8: Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

| | |
|---|---|
| Physical state | : Liquid. [Oily liquid.] |
| Appearance | : Clear. |
| Color | : Brown. |
| Odor | : Characteristic. |
| Odor threshold | : Not available. |
| pH | : 8 |
| Melting point/freezing point | : <-9°C |
| Initial boiling point and boiling range | : >300°C |
| Flash point | : Open cup: >204°C [ASTM D92.] |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : Not applicable. |
| Upper/lower flammability or explosive limits | : Not available. |
| Vapor pressure | : <0.01 kPa [room temperature] |
| Vapor density | : Not available. |
| Relative density | : 0.91 |
| Solubility(ies) | : Insoluble in the following materials: cold water and hot water. |
| Partition coefficient: n-octanol/ water | : Not available. |
| Auto-ignition temperature | : >300°C |
| Decomposition temperature | : >300°C |
| Viscosity (40°C) | : 162.9 cSt |
| Viscosity (100°C) | : 15.8 cSt |
| Explosive properties | : Not applicable. |
| Oxidizing properties | : Not applicable. |

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : Reactive or incompatible with the following materials:
Strong oxidizing materials

Q8 Mozart MS 50 SAE 40

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|---------------------------------|--------------------|-------------|----------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | LC50 Inhalation Dusts and mists | Rat - Male, Female | 5.53 mg/l | 4 hours |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| | LD50 Oral | Rat | >5000 mg/kg | - |

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|------------------------------------|---------|-------|----------|-------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Skin - Erythema/Eschar | Rabbit | 0.17 | 72 hours | 7 days |
| | Skin - Edema | Rabbit | 0 | 72 hours | 7 days |
| | Eyes - Iris lesion | Rabbit | 0 | 48 hours | 72 hours |
| | Eyes - Redness of the conjunctivae | Rabbit | 0.33 | 48 hours | 72 hours |

Conclusion/Summary : Not available.

Sensitization

| Product/ingredient name | Route of exposure | Species | Result |
|---|-------------------|------------|-----------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | skin | Guinea pig | Not sensitizing |

Conclusion/Summary : Not available.

Mutagenicity

| Product/ingredient name | Test | Experiment | Result |
|---|---|---|----------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | 474 Mammalian Erythrocyte Micronucleus Test | Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic | Negative |

Conclusion/Summary : Not available.

Carcinogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|------------------------|----------------|------|----------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Negative - Dermal - TC | Mouse - Female | - | 78 weeks |

Conclusion/Summary : Not available.

Reproductive toxicity

Q8 Mozart MS 50 SAE 40

SECTION 11: Toxicological information

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|---|-------------------|-----------|-------------------|--------------------|------------------|----------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Negative | Negative | Negative | Rat - Male, Female | Oral: 1000 mg/kg | - |

Conclusion/Summary : Not available.

Teratogenicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|-------------------|---------|------------|-----------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Negative - Dermal | Rat | 2000 mg/kg | 7 days per week |

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
dryness
cracking
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Q8 Mozart MS 50 SAE 40

SECTION 11: Toxicological information

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|--|--------------------|------------------------|---------------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | Sub-chronic NOAEL Oral | Rat - Male, Female | ≥2000 mg/kg | 13 weeks; 5 days per week |
| | Sub-acute LOAEL Oral | Rat - Male | 125 mg/kg | 13 weeks; 5 hours per day |
| | Sub-acute NOAEL Inhalation Dusts and mists | Rat - Male | >980 mg/m ³ | 4 weeks; 5 days per week |

Conclusion/Summary : Not available.

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : May damage fertility.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|---|-------------------|------------|------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | - | - | Inherent |

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---|--------------------|-----|-----------|
| Distillates (petroleum), solvent-dewaxed heavy paraffinic | >3 | - | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

Q8 Mozart MS 50 SAE 40

SECTION 12: Ecological information

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

European waste catalogue (EWC)

| Waste code | Waste designation |
|------------|---|
| 13 02 05* | mineral-based non-chlorinated engine, gear and lubricating oils |

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

| | ADR/RID | ADN | IMDG | IATA |
|--|----------------|----------------|----------------|----------------|
| 14.1 UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name | - | - | - | - |
| 14.3 Transport hazard class(es) | - | - | - | - |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | No. | No. |
| Additional information | - | - | - | - |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Q8 Mozart MS 50 SAE 40

SECTION 14: Transport information

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Restricted to professional users.

Other EU regulations

Europe inventory : Not determined.

| Product/ingredient name | Carcinogenic effects | Mutagenic effects | Developmental effects | Fertility effects |
|---|----------------------|-------------------|--------------------------------|-----------------------------|
| Branched alkylphenol and Calcium branched alkylphenol | - | - | Repr. 1B, H360D (Unborn child) | Repr. 1B, H360F (Fertility) |

Seveso II Directive

This product is not controlled under the Seveso II Directive.

Hazard class for water (WGK) : 2 Appendix No. 4

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

Australia : Not determined.

Canada : Not determined.

China : Not determined.

Japan : Not determined.

Malaysia : Not determined.

New Zealand : Not determined.

Q8 Mozart MS 50 SAE 40

SECTION 15: Regulatory information

| | |
|--------------------------|-------------------|
| Philippines | : Not determined. |
| Republic of Korea | : Not determined. |
| Taiwan | : Not determined. |
| United States | : Not determined. |

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|---|--------------------|
| Skin Sens. 1, H317 | Calculation method |
| Repr. 1B, H360FD (Fertility and Unborn child) | Calculation method |
| Aquatic Chronic 3, H412 | Calculation method |

Full text of abbreviated H statements :

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H360FD May damage fertility. May damage the unborn child. (Fertility and Unborn child)
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

Full text of classifications [CLP/GHS] :

- Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1
- Aquatic Chronic 1, H410 AQUATIC HAZARD (LONG-TERM) - Category 1
- Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM) - Category 3
- Aquatic Chronic 4, H413 AQUATIC HAZARD (LONG-TERM) - Category 4
- Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
- Repr. 1B, H360FD TOXIC TO REPRODUCTION (Fertility and Unborn child) - Category 1B
- Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2
- Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

Full text of abbreviated R phrases :

- R60- May impair fertility.
- R36/38- Irritating to eyes and skin.
- R43- May cause sensitization by skin contact.
- R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R53- May cause long-term adverse effects in the aquatic environment.

Full text of classifications [DSD/DPD] :

- Repr. Cat. 2 - Toxic to reproduction category 2
- Xi - Irritant
- N - Dangerous for the environment

Q8 Mozart MS 50 SAE 40

SECTION 16: Other information

Date of printing : 11-02-2015
Date of issue/ Date of revision : 11-02-2015
Date of previous issue : No previous validation
Version : 1
Prepared by : Kuwait Petroleum Research & Technology B.V., The Netherlands

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.