

# Q8 Outboard 2T

## Description

Two-stroke Outboard Motor Oil

## Application

- All outboard two-stroke gasoline engines (air or water cooled) with leadfree or leaded gasoline in self mixing or oil injection systems.

## Specifications

- NMMA TC-W3 Re- Certification number: RL-51030
- SAE J1536 Miscibility/Fluidity Grade 3

## Benefits

- Excellent cylinder protection against scuffing wear
- Protection against spark plug fouling and pre-ignition
- Protection against piston ring sticking and varnish deposits
- Reduced exhaust port deposits
- Excellent rust and corrosion protection
- Suitable for year round use in all climates

Properties	Method	Unit	Typical
Type	-	-	Self Mixing
Absolute Density, 15 °C	D 1298	kg/m <sup>3</sup>	867
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	38.6
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	6.5
Viscosity Index	D 2270	-	121
Sulfated Ash	D 874	% mass	nil
Flash Point, P-M	D 93	°C	84
Pour Point	D 97	°C	-39
Total Base Number	D 2896	mg KOH/g	3.8

*The figures above are not a specification. They are typical figures obtained within production tolerances.*