Q8 Schumann 460

Application
- Industrial gears

Specifications
- ISO 6743-3, categories DAA-DAB-DAG-DAH-DAJ and DVA
- DIN 51506, category VDL
- DIN 51517 part 3, category CLP

Benefits
- Extended drain periods of up to eight times mineral oils
- Compatible with mineral oils
- Compatible with normally used elastomers and plastic materials
- Energy saving and reduced oil consumption
- Reduced fire and explosion risks
- Less maintenance
- Outstanding low temperature startability
- Multi-purpose oil

References
- Q8 Schumann exceeds current Standards and manufacturer requirements for air compressor and gear lubricants

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	460
Absolute Density, 15 °C	D 4052	kg/m³	851
Kinematic Viscosity, 40 °C	D 445	mm²/s	460
Kinematic Viscosity, 100 °C	D 445	mm²/s	46.8
Viscosity Index	D 2270	-	159
Flash Point	D 92	°C	276
Pour Point	D 97	°C	-27
Ash	D 482	% mass	0.01
Sulfated Ash	D 874	% mass	0.04
Colour	D 1500	-	L1.0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Total Acid Number	D 974	mg KOH/g	0.72
Emulsion, Distilled Water, 82.2 °C		-	40-40-0(25)
Foam, 5 min blowing, seq. 1/2/3	D 892	ml	20/30/10
10 min settling, seq. 1/2/3		ml	0/0/0
Air Release, 50 °C	DIN 51381	min	15
FZG Test, A/8.3/90	DIN 51354	load stage	pass 12

The figures above are not a specification. They are typical figures obtained within production tolerances.