



## APPLICATIONS

**Eni Rotra MP/S 85W-90** is a special lubricant for gears with special E.P. (Extreme Pressure) and anti stick-slip characteristics, which makes it suitable for lubrication of the hypoid teeth in the limited slip differentials with blades and of axles with oil-bath brakes and clutches.

## CUSTOMER ADVANTAGES

- The special E.P. additivation used in this product guarantees the continuity of the lubrication film even when the gears are operated under particularly heavy and dynamic impulse loads with very high and intermittent sliding speeds between the teeth.
- The anti-slip additive contained in the product can modify the friction coefficient to prevent vibration phenomena in the clutch mechanism of the limited slip differential and in the oil immersed brakes used in the tractors.
- The anti-wear properties and strong greasiness considerably help to reduce the wear of gears and bearings.
- The particular oxidation stability avoids oil deterioration in parts operating at high temperature and effectively counteracts the tendency to increase viscosity and sludge formation.
- The strong anti-rust properties protect the gears and supports even in the presence of moisture.
- The strong anti-foam additivation conferred on the lubricant eliminates the negative consequences that excessive formation of foam would cause with regard to the continuity of the lubricant film.

## SPECIFICATIONS - APPROVALS

- ZF TE-ML 05C, 12C,16E, 21C
- API GL-5





## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	905
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	17.5
Viscosity at -12°C	ASTM D 2983	mPa·s	25000
Viscosity Index	ASTM D 2270	-	100
Flash point (COC)	ASTM D 92	°C	215
Pour point	ASTM D 97	°C	-24

