

Q8 Formula R Long Life 5W-30

Description

Ultra High Performance Low SAPS Synthetic Engine Oil for latest Renault Euro 5 & 6 engines equipped with a DPF.

Application

- Engine oil for Renault passenger car and commercial vehicle engines requiring LowSAPS oils.
- Extended drain intervals up to 30.000km.
- Specially developed for Renault Euro V diesel engines equipped with a DPF requiring RN 0720 engine oil specification.
- Only for Euro 5 & 6 engines requiring Low SAPS engine oil.

Specifications

ACEA C4

OEM Approvals

Renault RN 0720

Recommendations

MB 226.51

Benefits

- Reduces fuel consumption.
- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Density, 15 °C	D 4052	kg/m ³	852
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	67.3
Viscosity Index	D 2270	-	167
Apparent Viscosity, -30 °C	D 5293	mPa.s	6300
Pour Point	D 97	°C	-33
Flash Point	D 92	°C	203

The figures above are not a specification. They are typical figures obtained within production tolerances.

