

Q8 Garden Oil 30

Description

Gasoline engine oil for motorised garden and agricultural machines

Application

- In four-stroke gasoline engines operating under moderate to heavy duty endurance conditions and some transmissions where the engine oil quality has been defined according to one of the following specifications:

Specifications

- API CG-4/SJ
- ACEA B2/E2
- MAN 270 (diesel engines, normal drain)
- Mercedes-Benz 227.0
- Mercedes-Benz 228.0
- MTU (Oil type 1)
- ZF TE-ML 03
- Caterpillar TO-2 (transmissions)
- Voith (retarder)

Benefits

- Economical product for severe applications
- Keeps engine clean for easy starting and maximum performance
- Limits engine wear for extended the engine life
- Good protection against oxidation and oil thickening
- Prohibits corrosion and protects against rust
- Suitable as transmission lubricant in selected agricultural equipment

Properties	Method	Unit	Typical
Viscosity Grade			SAE 30
Absolute Density, 15 °C	D 1298	kg/m ³	891
Kinematic Viscosity, 40 °C	D 445	mm ² /s	99.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.3
Viscosity Index	D 2270	-	99
Borderline Pumping Temperature	D 3829	°C	-23
Flash Point, P-M	D 93	°C	202
Pour Point	D 97	°C	-27
Total Base Number	D 2896	mg KOH/g	7.5
Sulfated Ash Content	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

