

Q8 Heller 22

Application

- Off highway equipment and other hydraulic systems exposed to wide temperature fluctuations

Specifications

- DIN 51524 part 3, category HVLP
- ISO 11158, category HV
- AFNOR 48-603, category HV
- ISO 6743-4, category HR and HV
- DIN 51502, category HVLP

Benefits

- Optimum anti-wear performance, based on a zinc dialkyldithiophosphate additive
- Wide application temperature range through low pour point and outstanding low and high temperature viscosity characteristics
- Trouble-free operation due to the unique combination of outstanding demulsibility, foam, air release, hydrolytic stability and filterability
- Long term stable fluid viscosity through excellent shear stability characteristics of the selected viscosity index improver

References

- Q8 Heller meets the requirements of most off highway equipment manufacturers.

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	22
Absolute Density, 15 °C	D 4052	kg/m ³	858
Kinematic Viscosity, 40 °C	D 445	mm ² /s	22.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	4.98
Viscosity Index	D 2270	-	161
Flash Point	D 92	°C	190
Pour Point	D 97	°C	-36
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0(5)
Air Release, 50 °C	DIN 51381	min	1
Foam, 5 min blowing, seq. 1/2/3	D 892	ml	50/20/50
10 min settling, seq. 1/2/3		ml	0/0/0
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

