



ORLEN OIL AGRO STOU 10W-30

Quality class: API: CF-4/GL-4
ACEA: E2
ISO: HV
DIN: HVLP

GENERAL FEATURES:

Universal, multipurpose engine, gear and hydraulic oil for farming equipment.

APPLICATION:

ORLEN OIL AGRO STOU 10W-30 is mainly intended for farming equipment to lubricate engines, gears of various kinds, clutches, it can be used in wet brakes and hydraulic systems. It may be applied in Powershift gearboxes. It is recommended for Limited Slip systems.

STANDARDS, APPROVALS. SPECIFICATION:

It meets provision of the following:

John Deere J 27,
Massey Ferguson M1139, M1144,
Ford M2C 159B,
Ford 30/40 series,
Allison C-4,
Caterpillar TO-2,
ZF TE-ML 06B, 06C, 07B,
Mercedes-Benz 227.1, 228.1
Perkins

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	10W-30
kinematic viscosity at 100°C	mm ² /s	11.9
viscosity index	-	166
base value TBN	mg KOH/g	10.8
ignition temperature	°C	211
flow temperature	°C	-33

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

