SAFETY DATA SHEET

Q8 Vermeer WDA 220



SECTION 1: Identific undertaking	ation of the substance/mixture and of the company/
1.1 Product identifier	
Product name	: Q8 Vermeer WDA 220
Viscosity or Type	: ISO VG 220
Material uses	: Lubricating oil for industrial systems
1.2 Relevant identified uses Not applicable.	of the substance or mixture and uses advised against
1.3 Details of the supplier of	the safety data sheet
Manufacturer / Distributor	: Kuwait Petroleum Companies in the Benelux Company Office: Brusselstraat 59, B-2018, Antwerp Contactaddress: Petroleumkaai 7, B-2020, Antwerp Tel. +32 3 247 38 11, Fax +32 3 216 03 42
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communication preferably in English only.
1.4 Emergency telephone nu	ımber
Europe	: +44 (0) 1235 239 670
Global (English only)	: +44 (0) 1865 407 333

SECTION 2: Hazards identification

2.1 Classification of the sub	stance or mixture
Product definition	: Mixture
Classification according to	Regulation (EC) No. 1272/2008 [CLP/GHS]
The product is classified as	hazardous according to Regulation (EC) 1272/2008 as amended.
Aquatic Chronic 1, H410	
Ingredients of unknown toxicity	: None.
Ingredients of unknown ecotoxicity	: None.
Classification according to	Directive 1999/45/EC [DPD]
The product is classified as	dangerous according to Directive 1999/45/EC and its amendments.
Classification	: R52/53
Environmental hazards	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
See Section 16 for the full tex	t of the R phrases or H statements declared above.
See Section 11 for more deta	iled information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



ŝ

Q8 Vermeer WDA 220

SECTION 2: Hazards identification				
Signal word	:	Warning		
Hazard statements	:	H410 - Very toxic to aquatic life with long lasting effects.		
Precautionary statements				
General	:	Not applicable.		
Prevention	:	P273 - Avoid release to the environment.		
Response	:	P391 - Collect spillage.		
Storage	:	Not applicable.		
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.		
Supplemental label elements	:	Not applicable.		
Special packaging requirem	en	i <u>ts</u>		
Containers to be fitted with child-resistant fastenings	:	Not applicable.		
Tactile warning of danger	:	Not applicable.		
2.3 Other hazards				
Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.		
Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	Not applicable.		
Other hazards which do not result in classification	:	Defatting to the skin. Prolonged or repeated contact may dry skin and cause irritation.		

SECTION 3: Composition/information on ingredients

Identifiers	%			
		67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
REACH #: 01-2119480472-38 EC: 265-166-0 CAS: 64742-62-7 Index: 649-471-00-X	≥50 - <75	Not classified.	Not classified.	[2]
REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≥25 - <50	Not classified.	Not classified.	[2]
EC: 215-548-8	≥1 - <3	Repr. Cat. 3; R62	Repr. 2, H361fd (Fertility and Unborn child)	[1]
CAS: 1330-78-5		N; R50/53	Aquatic Acuté 1, H400 Aquatic Chronic 1, H410	
REACH #: 01-2119480433-40	≥0.3 - <1	N; R50/53	Aquatic Acute 1, H400	[1]
	01-2119480472-38 EC: 265-166-0 CAS: 64742-62-7 Index: 649-471-00-X REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6 EC: 215-548-8 CAS: 1330-78-5	$\begin{array}{llllllllllllllllllllllllllllllllllll$	$\begin{array}{c cccc} 01-2119480472-38\\ EC: 265-166-0\\ CAS: 64742-62-7\\ Index: 649-471-00-X\\ REACH #: \\ 01-2119471299-27\\ EC: 265-169-7\\ CAS: 64742-65-0\\ Index: 649-474-00-6\\ EC: 215-548-8 \\ \geq 1 - <3 \\ Repr. Cat. 3; R62\\ CAS: 1330-78-5 \\ REACH #: \\ \geq 0.3 - <1 \\ N; R50/53 \\ \end{array}$	REACH #: ≥50 - <75

Q8 Vermeer WDA 220

SECTION 3: Composition/information on ingredients			
EC: 204-881-4 CAS: 128-37-0	Aquatic Chronic 1, H410		
	See Section 16 for the full text of the R-phrases declared above.See Section 16 for the full text of the H statements declared above.		

The mineral oils in the product contain < 3% DMSO extract (IP 346).

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed <u>Potential acute health effects</u>

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure s</u>	igns/symptoms
Eye contact	: No specific data.

Date of issue/Date of revision

Q8 Vermeer WDA 220

Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.
4.3 Indication of any immed	iate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising	from the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst. This material is very toxic to aquatic life with long lasting effects. Fire water

5.1 Extinguishing media		
Suitable extinguishing media	Use dry chemical, CO_2 , alcohol-resistant foam or water spray (fog).	
Unsuitable extinguishing media	Do not use water jet.	
5.2 Special hazards arising	n the substance or mixture	
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may bur This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.	st.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the inci there is a fire. No action shall be taken involving any personal risk or without suitable training.	ident if
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressur mode. Clothing for fire-fighters (including helmets, protective boots and glove conforming to European standard EN 469 will provide a basic level of protective chemical incidents.	re s)

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Q8 Vermeer WDA 220

SECTION 6: Accidental release measures

6.3 Methods and materials for containment and cleaning up

	• •
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds (in tonnes)

Danger criteria				
Category	Notification and MAPP threshold	Safety report threshold		
E1: Hazardous to the aquatic environment - Acute 1 or Chronic 1	100	200		

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

Date of issue/Date of revision

Q8 Vermeer WDA 220

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredien	t name	Exposure limit values		
Residual oils (petroleum), solv Distillates (petroleum), solven paraffinic		Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist Lijst Grenswaarden / Valeurs Limites (Belgium, 11/2011). TWA: 5 mg/m ³ 8 hours. Form: mist STEL: 10 mg/m ³ 15 minutes. Form: mist		
Recommended monitoring procedures	atmosphere or of the ventilation protective equip the following: E the assessmen limit values and atmospheres - of exposure to of (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness in or other control measures and/or the necessity to use respiratory oment. Reference should be made to monitoring standards, such as European Standard EN 689 (Workplace atmospheres - Guidance for t of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment chemical and biological agents) European Standard EN 482 nospheres - General requirements for the performance of procedures ement of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be		
DNELs/DMELs No DNELs/DMELs available.				
PNECs No PNECs available.				
8.2 Exposure controls				
Appropriate engineering controls	: Good general contaminants.	ventilation should be sufficient to control worker exposure to airborne		
Individual protection measur	<u>'es</u>			
Hygiene measures	before eating, s Appropriate teo Wash contami	orearms and face thoroughly after handling chemical products, smoking and using the lavatory and at the end of the working period. chniques should be used to remove potentially contaminated clothing. nated clothing before reusing. Ensure that eyewash stations and a are close to the workstation location.		
Eye/face protection	assessment in gases or dusts	r complying with an approved standard should be used when a risk dicates this is necessary to avoid exposure to liquid splashes, mists, . If contact is possible, the following protection should be worn, essment indicates a higher degree of protection: safety glasses with		
Skin protection				
Hand protection	be worn at all t this is necessa check during u should be note different for diff several substate estimated. We	tant, impervious gloves complying with an approved standard should imes when handling chemical products if a risk assessment indicates ry. Considering the parameters specified by the glove manufacturer, se that the gloves are still retaining their protective properties. It d that the time to breakthrough for any glove material may be ferent glove manufacturers. In the case of mixtures, consisting of nces, the protection time of the gloves cannot be accurately ear suitable gloves tested to EN374. Recommended: <1 hour time): nitrile rubber 0.17 mm.		

Q8 Vermeer WDA 220

SECTION 8: Exposure controls/personal protection

-	
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	l a	nd chemical properties
<u>Appearance</u>		
Physical state	1	Liquid. [Oily liquid.]
Appearance	1	Clear.
Color	1	Yellow [Light]
Odor	4	Characteristic.
Odor threshold	4	Not available.
рН	4	7
Melting point/freezing point	1	<-12°C
Initial boiling point and boiling range	1	>300°C
Flash point	1	Open cup: >259°C [ASTM D92.]
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not applicable.
Upper/lower flammability or explosive limits	1	Not available.
Vapor pressure	1	<0.01 kPa [room temperature]
Vapor density	1	Not available.
Relative density	1	0.895
Solubility(ies)	1	Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	1	>300°C
Decomposition temperature	1	>300°C
Viscosity (40°C)	4	220 cSt
Viscosity (100°C)	÷	19 cSt
Explosive properties	;	Not applicable.
Oxidizing properties	÷	Not applicable.

9.2 Other information

No additional information.

Q8 Vermeer WDA 220

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours
	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
tris(methylphenyl) phosphate	LD50 Dermal	Rabbit	>10000 mg/kg	-
	LD50 Oral	Rat	3 g/kg	-
2,6-Di-tert-butyl-p-cresol	LD50 Oral	Rat	890 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
	Skin - Edema	Rabbit	0	72 hours	7 days
	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
tris(methylphenyl) phosphate		Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
2,6-Di-tert-butyl-p-cresol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Mild irritant	Human	-	48 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	48 hours 500 milligrams	-
Conclusion/Summary	: Not available.	<u> </u>	ł		

```
Not available.
```

Q8 Vermeer WDA 220

SECTION 11: Toxicological information Product/ingredient name Route of Species Result exposure Distillates (petroleum), skin Guinea pig Not sensitizing solvent-dewaxed heavy paraffinic

Conclusion/Summary

: Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Distillates (petroleum), solvent-dewaxed heavy paraffinic	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo	Negative
		Subject: Mammalian-Animal Cell: Somatic	

Conclusion/Summary : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal - TC	Mouse - Female	-	78 weeks

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

Conclusion/Summary : Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Negative - Dermal	Rat	2000 mg/kg	7 days per week

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contact		No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.
Ingestion	:	No known significant effects or critical hazards.

Q8 Vermeer WDA 220

SECTION 11: Toxicological information

Symptoms related to	the physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate : Not available. effects Potential delayed effects : Not available. Long term exposure Potential immediate : Not available.

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Product/ingredient name	e Result Species Dose Expos					
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week		
paranino	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day		
	Sub-acute NOAEL Inhalation Dusts and mists	Rat - Male	>980 mg/m³	4 weeks; 5 days per week		
Conclusion/Summary	: Not available.					
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.					
Carcinogenicity	: No known significant effects or critical hazards.					
Mutagenicity	: No known significant effects or critical hazards.					
Teratogenicity	: No known significant effects or critical hazards.					
Developmental effects	: No known significant effects or critical hazards.					
Fertility effects	: No known significant effects or critical hazards.					

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Algae - Stephanodiscus hantzschii - Exponential growth phase Daphnia - Daphnia magna	96 hours 48 hours
	48 hours
Fish - Gasterosteus aculeatus	96 hours
Er Fish - Gasterosteus aculeatus -	35 days
	48 hours
	ater Fish - Gasterosteus aculeatus - Egg r Daphnia - Daphnia pulex -

Q8 Vermeer WDA 220

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Inherent

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), solvent-dewaxed heavy paraffinic	>3	-	low
tris(methylphenyl) phosphate 2,6-Di-tert-butyl-p-cresol	5.11 5.1	794.328234724 1071.519305237	high high

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

PBT	: Not applicable.
vPvB	: Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
I I amount a sub-sub-sub-sub-sub-sub-sub-sub-sub-sub-	

Hazardous waste : Yes.

European waste catalogue (EWC)

Waste code	Waste designation		
13 01 10*	mineral based non-chlorinated hydraulic oils		
Packaging			
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		

Date of issue/Date of revision

Q8 Vermeer WDA 220

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Other EU regulations

Europe inventory

: Not determined.

: Not available.

Product/ingredient name	Carcinogenic effects	•	Developmental effects	Fertility effects
tris(methylphenyl) phosphate	-	-	Repr. 2, H361d (Unborn child)	Repr. 2, H361f (Fertility)

Seveso II Directive

This product is controlled under the Seveso II Directive.

Danger criteria

E1: Hazardous to the aquatic environment - Acute 1 or Chronic 1

Hazard class for water : 1 Appendix No. 4

(WGK)

Category

International regulations

Q8 Vermeer WDA 220

SECTION 15: Regulatory information							
Chemical Weapon Conve	ntion List Schedules I, II & III Chemicals						
Not listed.							
Montreal Protocol (Annex	<u>es A, B, C, E)</u>						
Not listed.							
Stockholm Convention on Persistent Organic Pollutants Not listed. Rotterdam Convention on Prior Inform Consent (PIC) Not listed.							
						UNECE Aarhus Protocol o	on POPs and Heavy Metals
						Not listed.	
						International lists	
National inventory							
Australia	: Not determined.						
Canada	: Not determined.						
China	: Not determined.						
Japan	: Not determined.						
Malaysia	: Not determined.						
New Zealand	: Not determined.						
Philippines	: Not determined.						
Republic of Korea	: Not determined.						
Taiwan	: Not determined.						
United States	: Not determined.						
15.2 Chemical Safety Assessment	: This product contains substances for which Chemical Safety Assessments are still required.						

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification			Justification
Aquatic Chronic 1, H410			Calculation method
Full text of abbreviated H statements	: H361fd (Fertility and Unborn child) H400 H410	Very toxic to aqu	umaging fertility. Suspected of damaging the unborn child. uatic life. uatic life with long lasting effects.

Q8 Vermeer WDA 220

SECTION 16: Other information				
Full text of classifications [CLP/GHS]	: Aquatic Acute 1, H400 AQUATIC HAZARD (ACUTE) - Category 1 Aquatic Chronic 1, H410 AQUATIC HAZARD (LONG-TERM) - Category 1 Repr. 2, H361fd (Fertility and Unborn child) TOXIC TO REPRODUCTION (Fertility and Unborn child) - Category 2			
Full text of abbreviated R phrases	 R62- Possible risk of impaired fertility. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 			
Full text of classifications [DSD/DPD]	: Repr. Cat. 3 - Toxic to reproduction category 3 N - Dangerous for the environment			
Date of printing	: 16-01-2015			
Date of issue/ Date of revision	: 16-01-2015			
Date of previous issue	: No previous validation			
Version	: 1			
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands			
Notice to reader				

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or

completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.