

Q8 Rembrandt 2

Description

MULTI-PURPOSE LITHIUM GREASE

Application

- Multi-purpose grease for industrial and automotive applications.
- Recommended for plain- and anti-friction bearings in:
 - electric motors
 - trucks
 - general machine lubrication
 - chassis lubrication
 - wheel bearings

Specifications

- Q8 Rembrandt 2 classifications:
- DIN 51502 K2K-30
ISO 6743 ISO-L-XCCEA2

Benefits

- Good roll stability
- Good rust-protection
- Long service life
- Wear protection for bearings operating moderate load and temperature conditions of between -25°C to +130°C
- Applicable in plain- and all types of anti-friction bearings
- Rust protection even in the presence of water

Properties	Method	Unit	Typical
Soap type	-	-	Lithium
Consistency, NLGI No.			NLGI 2
Penetration, Worked, 25 °C, 150 g, 5 s	D 217		
60 strokes	-	0.1 mm	288
10000 strokes	-	0.1 mm	292
Colour	Visual	-	brown
Dropping Point	D 566	°C	190
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Appearance	Visual	-	Smooth
Texture	Visual	-	<-- Long Fibres -->
Water Washout Resistance, 80 °C, 1 h	D 1264	%	<10
SKF Emcor Test	DIN 51802	-	pass
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	120

The figures above are not a specification. They are typical figures obtained within production tolerances.

