

Q8 Rembrandt EP 00

NLGI 00

Application

- Multi-purpose grease with EP properties for industrial and automotive applications.
- Recommended for highly loaded plain- and anti-friction bearings in:
- draglines
- bulldozers
- tractors
- excavators
- trucks
- hoisting equipment
- winches etc.

Specifications

- Q8 Rembrandt EP 00 classifications:
- DIN 51502 KP00K-30
ISO 6743 ISO-L-XCCHB00

Benefits

- Excellent roll stability
- Long service life
- Temperature resistant up to 110 °C for Q8 Rembrandt EP0 and EP00, and up to 130 °C for Q8 Rembrandt EP1 and EP2
- Excellent anti-wear properties especially for bearings operating under shock load or vibrating conditions
- Excellent rust-protection even in the presence of water
- Easy pumpability due to its smooth structure

Properties	Method	Unit	Typical
Soap type	-	-	Lithium
Consistency, NLGI No.			NLGI 00
Penetration, Worked, 25 °C,			
150 g, 5 s	D 217		
60 strokes		0.1 mm	415
10000 strokes	-	0.1 mm	415
Colour	Visual	-	brown
Dropping Point	D 566	°C	170
Copper Corrosion, 100 °C, 24 h	D 4048	-	pass
Appearance	Visual	-	Smooth
Texture	Visual	-	Long Fibres
Water Washout Resistance,			
80 °C, 1 h	D 1264	%	<5
Water Resistance, 90 °C, 3 h	DIN 51807	-	pass
SKF Emcor Test	DIN 51802	-	pass
SKF R2F Test, conditions A	-	-	pass
Four Ball Test, Weld Load	IP 239	N	2450
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	280
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	-

The figures above are not a specification. They are typical figures obtained within production tolerances.

