

Q8 T 45 LS 85W-140

Description

Automotive rear axle lubricant

Application

- In rear axles especially those incorporating limited slip differentials

Recommendations

- Q8 T 45 LS may be used as gear lubricant in hypoid gears, rear axles and final drives especially those equipped with limited slip differential, when one or more of the following specifications are used to describe the required lubricant quality:

Specifications

- API GL-5
- MIL-L-2105B
- Ford ESW-M2C119-A (locking differential hypoid rear axle gears, conventional and/or locking front and rear hypoid axles)
- ESP-M2C154-A (locking or conventional differential hypoid rear axles)
- General Motors Pt. no. 19 42 382 (90 006 326) (rear axles with or without limited slip)
- Hanomag Specification 511 (limited slip rear axles)
- Volvo 97311 (final drives in cars equipped with limited slip)
- ZF TE-ML 05C (axles with multiple-disc limited-slip differentials or with wet brakes)
- ZF TE-ML 12C
- ZF TE-ML 16E (Transmissions for rail vehicles)
- ZF TE-ML 21C

Benefits

- Incorporates special friction modifier system to obtain optimal limited slip function
- Reduces axle noise
- Extends axle life
- Protects against gear wear
- Prohibits corrosion
- Protects against rust

Properties	Method	Unit	Typical
Viscosity Grade			SAE 85W-140
Absolute Density, 15 °C	D 1298	kg/m ³	910
Kinematic Viscosity, 40 °C	D 445	mm ² /s	376
Kinematic Viscosity, 100 °C	D 445	mm ² /s	27.1
Viscosity Index	D 2270	-	97
Brookfield Viscosity, -12 °C	D 2983	Pa.s	<150
Brookfield Viscosity, -26 °C	D 2938	Pa.s	
Pour Point	D 97	°C	-21
Flash Point, P-M	D 93	°C	>200

The figures above are not a specification. They are typical figures obtained within production tolerances.