

Q8 T 630 5W-30

Description

Fuel efficient SAE 5W-30 Synthetic Engine Oil

Application

- Engine oil for passenger cars with normally aspirated or turbocharged gasoline, LPG or diesel engines.
- Specially recommended where a high quality engine oil with demonstrated fuel consumption reduction is required.
- Specially recommended for Mazda Rotary engines in Mazda RX-7 and RX-8 models.

Specifications

- ACEA A1/B1
- ACEA A5/B5

Benefits

- Year round passenger car engine lubricant
- Excellent engine protection after cold starting
- Extended engine oil drain interval capability
- Demonstrated engine fuel consumption reduction
- Provides high oil film strength limiting engine wear
- Excellent engine performance at all driving conditions
- Good protection against rust and corrosion
- Prevents formation of black sludge
- Low volatility reduces oil consumption
- Reduced environmental impact
- Catalyst friendly lubricant

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m ³	863
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.61
Kinematic Viscosity, 40 °C	D 445	mm ² /s	54.1
Viscosity Index	D 2270		164
Apparent Viscosity, -30 °C	IP 383	mPa.s	6050
Pour Point	D 97	°C	-30
Flash Point	D 93	°C	201
Total Base Number	D 2896	mg KOH/g	10.1

The figures above are not a specification. They are typical figures obtained within production tolerances.

