



PLATINUM GEAR GL-4 80W

Quality class: API: GL-4
Viscosity grad: SAE: 80W

GENERAL FEATURES:

Platinum Gear GL-4 80W is a high quality gear oil based on deep refined mineral oils. It is featured by excellent lubricating properties, high resistance to oxidation and high ability to transfer loads. Platinum Gear GL-4 80W guarantees very good antiwear properties and it is a perfect protection against rust and corrosion.

APPLICATION:

Platinum Gear GL-4 80W is intended to lubricate manual gear boxes and other gears of vehicles operating in difficult conditions i.e. high speed and low torque or low speed and high torque. It is also recommended for all machines and devices, manufacturer of which recommends API GL-4 gear oil.

Platinum Gear GL-4 80W was included on the list of oils ZF TE-ML 02B, 17A and corresponds to ZF TE-ML 16A, 19A quality level.
Platinum Gear GL-4 80W replaced Hipol 10 ZF.

STANDARDS, APPROVALS. SPECIFICATION:

MAN 341 Type Z2
MAN 341 Type E1
MB-Approval 235.1
ZF TE-ML 02B, 17A

It meets provision of:
ZF TE-ML 16A, 19A

| PARAMETERS | UNIT | TYPICAL VALUES |
|------------------------------|--------------------|----------------|
| Kinematic viscosity at 100°C | mm ² /s | 9.6 |
| Viscosity index | - | 97 |
| Flow temperature | °C | -29 |
| Ignition temperature | °C | 218 |

NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

