

## PLATINUM GEAR LX 85W-140

Quality class: API: GL-5  
Viscosity grad: SAE: 85W-140

### GENERAL FEATURES:

Platinum Gear LX 85W-140 is a high-performance gear oil designed for trucks, construction and agricultural machines. Due to the good oxidation resistance and carrying high loaded capacity provides protection of transmission elements during the entire operation.

#### Guarantees:

- stability of the lubricating properties during operation
- High load carrying capacity,
- Excellent lubricity and anti-wear properties.

### APPLICATION:

Platinum Gear LX 85W-140 is intended for use primarily in final drives and rear axles.

### STANDARDS, APPROVALS. SPECIFICATION:

#### Meet requirements:

ZF TE-ML 05A, 07A, 08, 12E, 16BD, 17B, 19B, 21A, 02A, 02B, 17A

Scania STO 1:0

Volvo 1273.10

| PARAMETERS                   | UNIT               | TYPICAL VALUES |
|------------------------------|--------------------|----------------|
| SAE Viscosity grade          | -                  | 85W-140        |
| Kinematic viscosity at 100°C | mm <sup>2</sup> /s | 27,5           |
| Viscosity index              | -                  | 95             |
| Solidification point         | °C                 | -23            |

#### NOTE:

Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

