



PLATINUM MINERAL 15W-40

Quality class: API: SL/CF
ACEA : A3/B3, A3/B4
Viscosity grad: SAE: 15W-40

GENERAL FEATURES:

Platinum Mineral 15W-40 is a mineral, multiseasonal engine oil developed with Complex Protection Formula which offers full guarantee of protection of engine in all operation conditions. Unique formulation provides perfect oil performance, reduction of valves wear and at the same time higher control of residue content. Exceptional quality of applied mineral base oil and very good antioxidative properties guarantees unique engine protection and lower oil consumption. It perfectly prevents deposits formation.

APPLICATION:

It is intended to be used round the year in modern cars and LCVs with both petrol and diesel engines equipped with a catalyst.

STANDARDS, APPROVALS. SPECIFICATION:

MB-Approval 229.1
It meets provision of the following:
VW 505 00

PARAMETERS	UNIT	TYPICAL VALUES
SAE viscosity grade	-	15W-40
kinematic viscosity at 100°C	mm ² /s	14.2
HTHS viscosity at 150°C	MPa·s	3.8
viscosity index	-	141
flow temperature	°C	- 30
ignition temperature	°C	224
base value TBN	Mg KOH/g	8.0
sulphate ash	%	1.0

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

