

Q8 Formula Ultra V 0W-20

Description

Synthetic Low SAPS SAE 0W-20 Passenger Car Engine Oil for Volvo Euro 6 engines with demonstrated Fuel Economy Improvement

Application

- Specially developed for Volvo Euro 6 passenger car engines requiring Volvo VCC RBS0-2AE

Specifications

- Volvo VCC RBS0-2AE 0W-20

Benefits

- Specially developed for reducing fuel consumption
- Up to 3.4% Fuel Economy Improvement demonstrated in M111 FE engine test
- Low SAPS technology for Euro 6 exhaust gas after treatment system protection
- Excellent engine protection after cold starting
- Extended oil drain interval capability
- Excellent engine performance at all driving conditions
- Outstanding protection against foam formation, rust and corrosion

Properties	Method	Unit	Typical
Viscosity Grade			SAE 0W-20
Absolute Density, 15 °C	D 4052	kg/m ³	845
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.2
Kinematic Viscosity, 40 °C	D 445	mm ² /s	48.7
Viscosity Index	D 2270	-	175
Apparent Viscosity, -35 °C	D 5293	mPa.s	5700
Pour Point	D 97	°C	-45
Flash Point	D 92	°C	204
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>2.6

The figures above are not a specification. They are typical figures obtained within production tolerances.

