

Q8 Rodin EP 415

Description

HIGH PERFORMANCE CALCIUM SULPHONATE COMPLEX GREASE

Application

- Q8 Rodin EP 415 is suitable for heavily loaded applications and in wet and corrosive environments.
- It is a modern high performance product suitable for industrial, marine and off road applications.

Specifications

- DIN 51502 classification: KP1.5N-20
- ISO 6743 classification: ISO-L-XB(F)DIB1.5

Benefits

- Excellent mechanical stability
- Excellent wear protection due to the functional soap
- Good corrosion protection
- Excellent resistance against water

Properties	Method	Unit	Typical
Consistency, NLGI No.	-	-	1.5
Colour	Visual	-	Brown
Base fluid type	-	-	Mineral base oil
Soap type	-	-	Calcium sulphonate complex
Penetration, Worked, 25 °C, 150 g, 5 s	D 217	-	
60 strokes	-	0.1 mm	290-320
Dropping Point	D 566	°C	>300
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	400
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	23
SKF Emcor Test, WWO synth. salt water	ISO 11007	-	1-90
Water Resistance, 90 °C, 3 h	DIN 51807	-	max 1-1
Four Ball, Weld Load	IP 239	N	5000N

The figures above are not a specification. They are typical figures obtained within production tolerances.

