

Q8 Stravinsky AB 100

ISO VG 100

Application

- Synthetic refrigeration compressor lubricant based on AlkylBenzene
- Q8 Stravinsky AB is suitable for use in both reciprocating and screw compressors

Recommendations

- Suitable for use with CFC, HCFC and traditional refrigerants (e.g. ammonia)

Specifications

- ISO 6743-3, categories DRA, DRB and DRC

Benefits

- Outstanding thermal stability in combination with a high flash point which ensures problem-free operation across a wide temperature range
- Excellent oxidative and chemical stability which ensures stable operating conditions, minimizes sludge and deposit formation and reduces downtime
- Improved lubricity and superior load carrying capacity which maximizes compressor lifetime and improves system efficiency
- Good compatibility with seal materials normally used in refrigeration equipment

Caution

- Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky AB it is recommended to flush the compressor lubricant system
- Q8 Stravinsky AB is not suitable for HFC (e.g. R134a)

Properties	Method	Unit	Typical
Grade	-	-	bright and clear
Appearance		Visual	ISO VG 100
Absolute Density, 15 °C	D 4052	kg/m ³	870
Kinematic Viscosity, 40 °C	D 445	mm ² /s	100
Flash Point, COC	D 92	°C	195
Pour Point	D 97	°C	-27
Colour	D 1500	-	L 0.5

The figures above are not a specification. They are typical figures obtained within production tolerances.

