

# Q8 Goya NT 320

## Application

- Industrial gear drives, specifically severe applications such as windmill gears

## Specifications

- DIN 51517 part 3, category CLP
- ISO 12925-1, type CKC-CKD
- AGMA 9005-E02
- Jahn timer-Kestermann Getriebewerke GmbH & Co. KG

## Benefits

- Top quality industrial gear oil
- Long life due to outstanding oxidation and thermal stability
- Compatible with normally used seal materials
- Energy saving and friction reduction
- Wear protection under the most severe conditions
- Reduced wear under boundary lubrication conditions

## References

- Q8 Goya NT exceeds current Standards for gear lubricants, and provides highest obtainable performance in the grey staining test
- Q8 Goya NT is approved by Jahn timer-Kestermann for industrial gears and windturbine gear applications.

Properties	Method	Unit	Typical
ISO Viscosity Grade	-	-	320
Absolute Density, 15 °C	D 4052	kg/m <sup>3</sup>	897
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	320
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	24.22
Viscosity Index	D 2270	-	96
Flash Point	D 92	°C	248
Pour Point	D 97	°C	-12
Rust Test, Procedure A, 24 h	D 665	-	pass
Total Acid Number	D 974	mg KOH/g	1.1
Foam, 5 min blowing, seq. 1/2/3	D 892	ml	20/10/20
10 min settling, seq. 1/2/3		ml	0/0/0
FZG Test, A/8.3/90	DIN 51354	load stage	Pass 14
FZG Test, A/16.6/90	DIN 51354	load stage	Pass 12
FZG Test, A/16.6/140	DIN 51354	load stage	12
FZG Grey Staining Test, 90 °C	FVA 54/7	load stage	Pass 10
FZG Grey Staining Test, 60 °C	FVA 54/7	load stage	Pass 10

The figures above are not a specification. They are typical figures obtained within production tolerances.

