

Q8 T 630 DPF 5W-30

Description

Ultra High Performance Low SAPS SAE 5W-30 Synthetic Engine Oil for Euro 4, 5 and 6 engines for normal and extended drain intervals.

Application

- For passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 4, 5 and 6 engines requiring LowSAPS engine oil.

Specifications

- ACEA C3
- API SN/CF
- VW 502.00/505.01
- MB 229.51
- BMW Longlife-04
- ACEA C2 suitable for use

Benefits

- LowSAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter.
- Excellent engine cleanliness and wear protection increasing engine durability.
- Reduces fuel consumption.
- Extended drain interval capability.

Properties	Method	Unit	Typical
Viscosity Grade			SAE 5W-30
Absolute Density, 15 °C	D 4052	kg/m ³	853
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.2
Kinematic Viscosity, 40 °C	D 445	mm ² /s	66.5
Viscosity Index	D 2270	-	166
Apparent Viscosity, -30 °C	D 5293	mPa.s	6300
Sulphated Ash	D 280	% mass	0.8
Pour Point	D 97	°C	-36
Flash Point	D 92	°C	210

The figures above are not a specification. They are typical figures obtained within production tolerances.