



## APPLICATIONS

**Eni OSO 32** is a high performance antiwear hydraulic oil, specifically designed to meet the most rigorous performance requirements of a wide range of hydraulic system and component manufacturers.

It's formulated with selected base oils treated with "low zinc" technology ensuring excellent antiwear, antirust and antioxidant properties. It has an outstanding filterability in service.

**Eni OSO 32** is also suitable for other duties in which lubricants of high oxidation stability and lubrication performance are required, allowing use of a single product with excellent performance characteristics.

## CUSTOMER ADVANTAGES

- Ensures long re-lubrication intervals thanks to very high termo-oxidative stability
- Suitable for hydraulic systems with very thin filters (3 microns)
- Maximizes water removal system efficiency thanks to excellent demulsibility
- Protects components reducing downtime thanks to outstanding antiwear property
- Helps prevent aeration and cavitation damage in low residence time systems thanks to rapid air release
- Minimizes deposits formation contributing to system cleanliness

## SPECIFICATIONS & APPROVALS

- BS 4231 HSD
- Fives Cincinnati P-68 level
- Eaton Vickers I-286-S
- Denison HF-0 level
- REXROTH RD 90220-01/12.10
- ATOS Table P002-1/E
- DIN 51524-2 HLP
- ISO 11158 HM





- AFNOR NF E 48603 HM

## CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	875
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	32
Viscosity index	ASTM D 2270	-	109
Flash point (COC)	ASTM D 92	°C	224
Pour point	ASTM D 97	°C	-27
Demulsibility at 54°C	ASTM D 1401	mins	20
Foaming (sequence I)	ASTM D 892	cc/cc	20/0

